



## MATERIAL SAFETY DATA SHEET

**Section 1: Product and Company Identification**

**Product Group:** Finishing Products, Ready-Mix Joint Compounds and Ready-Mix Non-Aggregated Textures

**Product Use:** Ready Mix Drywall Finishing

<b>Manufacturer:</b>	BPB America Inc. 5301 West Cypress St., Suite 300 Tampa, FL 33607-1766 Web Site: <a href="http://www.bpb-na.com">www.bpb-na.com</a>	BPB Canada Inc. 2424 Lakeshore Road West, Mississauga, Ontario, Canada L5J 1K4 Web Site: <a href="http://www.bpb-na.com">www.bpb-na.com</a>
----------------------	---	---

<b>Phone Number:</b>	Phone: +1-813-286-3900 Customer Response Center 1-866-4 BPB USA (1-866-427-2872)	Telephone: 905-823-9881 Fax: 905-823-4860
----------------------	--	--

<b>Product Names:</b>	<u>US Product Line:</u> ProFin® All-Purpose ProFin® Taping ProFin® Finishing ProFin® LITE All-Purpose ProFin® LITE Finishing ProFin® LITE Taping ProFin® Multi-Purpose ProFin® LITE Multi-Purpose ProFin® EXTRA ProFin® ULTRA ProFin® ONE ProFin® Easi-Tex Spray Texture	<u>Canadian Product Line:</u> ProFin® Regular Multi-Purpose ProFin® 2-KOTE Plus Multi-Purpose ProFin® ULTRA White Multi-Purpose ProFin® ULTRA Beige Multi-Purpose ProFin® EXTRA White Multi-Purpose ProFin® EXTRA Beige Multi-Purpose ProFin® Finishing ProFin® LITE Taping ProFin® LITE Finishing ProFin® LITE All-Purpose ProFin® ONE Multi-Purpose Easi-Fil™ Multi-Purpose ProFin® Reinforced LITE Spray Texture ProFin® Spray LITE Ready-Mix Texture The Best Mud In The Joint®: All-Purpose, Taping, Finishing and Elite.
-----------------------	--	--

**24-hour Emergency Number:** In case of an emergency call  
 Team-1 Environmental Services Inc.  
 1-800-32 SPILL; 1-800-327-7455 (24 hrs)

**Section 2: Hazards Identification**

NFPA (USA)	WHMIS (Canada)	Transport Symbol
		<p><b>Not Regulated for Transportation</b></p>

## Section 2: Hazards Identification, continued

<b>Emergency Overview:</b>	<p>BPB Ready-Mix Joint Compounds and Ready-Mix Non-Aggregated Textures do not present an inhalation, ingestion, or contact health hazard unless subjected to operations such as sanding or machining which result in the generation of airborne particulate.</p> <p><b>Appearance, Colour and Odour:</b> Water-based paste, white to light grey, odourless.</p> <p><u>USA:</u> This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).</p> <p><u>Canada:</u> This product is a controlled product under WHMIS.</p>
<b>Potential Health Effects:</b>	<p><b>ACUTE (short term): see Section 8 for exposure controls</b></p>
<b>Relevant Route(s) of Exposure:</b>	<p>Inhalation, Skin contact, Eye contact</p>
<b>Inhalation:</b>	<p>High concentrations of dust from sanding or machining, may cause coughing and mild, temporary irritation following a short-term exposure. Long-term inhalation exposure to crystalline silica can have potentially serious respiratory effects (see Chronic health effects below).</p>
<b>Ingestion:</b>	<p>Avoid ingesting this product. Ingestion may cause gastrointestinal problems.</p>
<b>Skin:</b>	<p>Prolonged or repeated contact may cause irritation.</p>
<b>Eye:</b>	<p>Direct contact with the eyes may cause temporary irritation as a foreign object in the eye.</p> <p><b>CHRONIC (long term): see Section 11 for additional toxicological data</b> Prolonged or repeated exposure to fine airborne crystalline silica dust may cause severe scarring of the lungs, a disease called silicosis. The risk of developing and the severity of silicosis depends on the airborne concentration of respirable-size silica dust to which an employee is exposed and the duration of exposure. Silicosis usually develops gradually over 20 years or more of exposure. Particles with diameters less than 1 micrometer are considered most hazardous. The amount of respirable silica generated from sanding operations will vary.</p> <p>The early symptoms of silicosis are cough, mucous production and shortness of breath upon exertion. Silicosis may continue to develop even after exposure to crystalline silica has stopped.</p> <p>The International Agency for Research on Cancer (IARC) has concluded that crystalline silica in the form of quartz from occupational sources should be classified as carcinogenic to humans (Group 1).</p>
<b>Medical Conditions Aggravated by Exposure:</b>	<p>Skin contact may aggravate an existing dermatitis.</p>
<b>Interactions With Other Chemicals:</b>	<p>Tobacco smoking in combination with long-term high dust exposures may increase both smoking and dust-related pulmonary health problems.</p> <p>Simultaneous exposure to known carcinogens can increase the carcinogenicity of crystalline silica.</p>
<b>Potential Environmental Effects:</b>	<p>No adverse effects known.</p>

### Section 3: Composition / Information on Ingredients

#### Hazardous Ingredients:

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Wt.%</u>
Limestone	1317-65-3	60 - 90
Mica	12001-26-2	7 - 13
Kaolin clay	1332-58-7	7 - 13
Talc	14807-96-6	1 - 4
Attapulgite	12174-11-7	1 - 3
Crystalline silica (Quartz)**	14808-60-7	1 - 5**
Ethylene glycol	107-21-1	0.1 - 0.7

\*\* Total Crystalline silica, as quartz.

**Note:** See Section 8 of this MSDS for exposure limit data for these ingredients.

### Section 4: First Aid Measures

- Inhalation:** If high airborne concentrations are present, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). If symptoms develop, remove source of contamination or move victim to fresh air. Obtain medical advice.
- Eye Contact:** Do not allow victim to rub eyes. Let the eyes water naturally for a few minutes. Have victim look right and left, and then up and down. If particle/dust does not dislodge, flush with lukewarm, gently flowing water for 5 minutes or until particle/dust is removed, while holding the eyelids open. If irritation persists, immediately obtain medical attention. DO NOT attempt to manually remove anything stuck to the eye.
- Skin Contact:** No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
- Ingestion:** If irritation or discomfort occurs, obtain medical attention immediately.
- Notes to Physician:** Jurisdictions which have specific regulations for crystalline silica also require medical surveillance programs. Medical surveillance programs may include periodic physical examinations, chest X-rays and pulmonary function tests. Since there may be some variation in these requirements, specific information should be sought from the appropriate government agency in each jurisdiction.

## Section 5: Fire Fighting Measures

<b>Flammable Properties:</b>	Product is non-flammable and does not support combustion.
<b>Suitable extinguishing Media:</b>	Use water or other extinguishing media appropriate for the surrounding fire.
<b>Unsuitable extinguishing Media:</b>	Not available
<b>Explosion Data:</b>	
<b>Sensitivity to Mechanical Impact:</b>	Not sensitive
<b>Sensitivity to Static Discharge:</b>	Not sensitive
<b>Specific Hazards arising from the Chemical:</b>	Calcium carbonate may decompose into corrosive calcium oxide and carbon dioxide at about 825°C (1517°F).
<b>Protective Equipment and precautions for firefighters:</b>	As for any fire, evacuate the area and fight the fire from a safe distance. Wear a pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire from a protected location or a safe distance.
<b>NFPA</b>	
<b>Health:</b>	1
<b>Flammability:</b>	0
<b>Instability:</b>	0

## Section 6: Accidental Release Measures

<b>Personal Precautions:</b>	Wear proper personal protective equipment as indicated in Section 8.
<b>Environmental Precautions:</b>	Prevent material from contaminating soil and from entering sewers or waterways.
<b>Methods for Containment:</b>	No special methods required.
<b>Methods for Clean-up:</b>	Scoop or shovel spilled material into an appropriate waste container for disposal. Collect all spilled material for proper disposal. Dispose in accordance with federal, state and local regulations.
<b>Other Information:</b>	Not available

## Section 7: Handling and Storage

<b>Handling:</b>	Avoid creating and breathing dust from this product. Wet sand when possible. Avoid contact with eyes, skin and clothing. Minimize dust generation and accumulation. Wear protective glasses and gloves. If exposure limits are exceeded wear appropriate respiratory protection. (See Section 8)
<b>Storage:</b>	KEEP OUT OF REACH OF CHILDREN. Store product in its original container. Keep from freezing and extreme heat. Keep container closed when not in use. See Section 13 for disposal considerations.

**Section 8: Exposure Controls/Personal Protection**

**Exposure Guidelines**

<u>Ingredient</u>	<u>ACGIH TLV (8-hr. TWA) (mg/m<sup>3</sup>)</u>	<u>U.S. OSHA PEL (8-hr. TWA) (mg/m<sup>3</sup>)</u>	<u>Ontario (Canada) TWAEV (mg/m<sup>3</sup>)</u>
Limestone	10	15 (total dust) 5 (respirable fraction)	10
Mica	3 (respirable)	20 mppcf* (less than 1% crystalline silica)	3 (respirable)
Kaolin clay	2 (respirable)	15 (total dust) 5 (respirable fraction)	2 (respirable)
Talc	2 (respirable)	20 mppcf* (less than 1% crystalline silica)	2 (respirable)
Attapulgite	Not established	Not established	Not established
Crystalline silica (Quartz)	0.025 (respirable)	quartz (total dust): 30 mg/m <sup>3</sup> / (%SiO <sub>2</sub> + 2) quartz (respirable): 10 mg/m <sup>3</sup> / (%SiO <sub>2</sub> + 2)	0.05 (respirable) Designated Substance in Ontario
Ethylene glycol	100 Ceiling	Not established	100 CEV

\*mppcf: Million particles per cubic foot of air.

**Exposure Controls**

**Other Exposure Guidelines:** For Kaolin Clay: NIOSH REL 10 mg/m<sup>3</sup> (total dust); 5 mg/m<sup>3</sup> (respirable dust)

**Engineering Controls:** General ventilation is adequate for application of product in its original form. During sanding operations, monitor dust concentrations in air and provide local exhaust ventilation when any exposure guideline is exceeded.

**Personal Protection:**

**Eye/Face Protection:** Wear safety glasses or goggles. During sanding operations wear protective goggles.

**Skin Protection:** Wear protective gloves when necessary to prevent irritation to the skin.

**Respiratory Protection:** During sanding operations and when dust concentrations in air exceed the occupational exposure guidelines, always take the following precautions:

- Wear a NIOSH approved dust mask.
- Maintain adequate ventilation and air circulation.
- Warn others in the area.
- Use a NIOSH approved respirator when dust levels exceed any of the exposure guidelines listed in the table above.

NIOSH recommendations for Crystalline silica (respirable dust); concentrations in air:

UP TO 0.5 mg/m<sup>3</sup>: Air-purifying respirator with high-efficiency particulate filter(s).

UP TO 1.25 mg/m<sup>3</sup>: Powered air-purifying respirator with high-efficiency particulate filter; or SAR operated in a continuous-flow mode.

UP TO 2.5 mg/m<sup>3</sup>: Full-facepiece air-purifying respirator with high-efficiency particulate filter(s); or powered air-purifying respirator with tight-fitting facepiece and high-efficiency particulate filter.

UP TO 25 mg/m<sup>3</sup>: Positive pressure SAR.

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or Canadian Standards Association (CSA) Standard Z94.4-93 must be followed whenever workplace conditions warrant a respirator's use.

**Other Protective Equipment:** Not applicable

**General Hygiene Measures:** Launder contaminated clothing before re-wearing, or discard. Do not eat, drink or smoke in work areas. Wash hands thoroughly after handling this material. Maintain good housekeeping.

**Section 9: Physical and Chemical Properties**

<b>Physical State:</b>	Paste	<b>Flash Point &amp; method:</b>	Not applicable
<b>Appearance, Colour and Odour:</b>	Water-based paste, white to light grey, odourless.	<b>Autoignition Temperature:</b>	Not applicable
<b>Odour Threshold:</b>	Not available	<b>Flammability Limits in Air:</b>	Not applicable
<b>pH:</b>	7 – 8.5	<b>Vapour Pressure:</b>	Not available
<b>Specific Gravity: (water = 1)</b>	0.8 – 1.7	<b>Vapour Density: (Air = 1)</b>	Not available
<b>Partition coefficient: (n-octanol/water)</b>	Not available	<b>Evaporation Rate: (n-Butyl Acetate = 1)</b>	Not available
<b>Solubility:</b>	Slightly soluble in water	<b>Boiling Point/Range:</b>	Similar to water (100°C approximate)
<b>Viscosity:</b>	Not available	<b>Melting Point:</b>	Similar to water (< 0°C approximate)
<b>Decomposition Temperature:</b>	825°C (1517°F)		

**Section 10: Stability and Reactivity**

<b>Chemical Stability:</b>	Stable
<b>Conditions to Avoid:</b>	Not available
<b>Incompatible Materials:</b>	Strong acids, Aluminum and Ammonium salts. May react with strong acids to liberate carbon dioxide.
<b>Hazardous Decomposition Products:</b>	Calcium oxide may form if product is exposed to extreme heat 825°C (1517°F).
<b>Possibility of Hazardous Reactions:</b>	None known

**Section 11: Toxicological Information**

**Acute Toxicity Data**

	<b>LD<sub>50</sub> Oral</b> (mg/kg)	<b>LD<sub>50</sub> Dermal</b> (mg/kg)	<b>LC<sub>50</sub> Inhalation</b> (4 hrs.)
Limestone	6 450 (rat)	Not available	Not available
Mica	Not available	Not available	Not available
Kaolin clay	Not available	Not available	Not available
Talc	Not available	Not available	Not available
Attapulgate	Not available	Not available	Not available
Crystalline silica (Quartz)	Not available	Not available	Not available
Ethylene glycol	1 650 (cat)	9 500 (rabbit)	Not available

**Chronic Toxicity Data**

**Carcinogenicity:**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

	<b>ACGIH</b>	<b>IARC</b>	<b>NTP</b>
Limestone	Not listed	Not listed	Not listed
Mica	Not listed	Not listed	Not listed
Kaolin clay	A4	Not listed	Not listed
Talc	A4	Group 3	Not listed
Attapulgate	A4	Group 2B (fibre <5um) Group 3 (fibre >5um)	Not listed
Crystalline silica (Quartz)	A2	Group 1	Known
Ethylene glycol	A4	Not listed	Not listed

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2: Suspected human carcinogen

A4: Not classifiable as a human carcinogen

IARC: (International Agency for Research on Cancer)

Group 1: The agent is carcinogenic to humans

Group 2B: The agent is possibly carcinogenic to humans

Group 3: The agent is not classifiable as to its carcinogenicity in humans

NTP: (National Toxicity Program)

Known – Known to be a human carcinogen

**Irritation:**

Inhaling high concentrations of dust may cause coughing and mild, temporary irritation. Irritating to the eyes as a foreign object. May be irritating to the skin.

**Corrosivity:**

Not applicable

**Sensitization:**

Not applicable

**Neurological Effects:**

Not applicable

**Genetic Effects:**

Not applicable

**Reproductive Effects:**

Not applicable

**Developmental Effects:**

Ingestion of ethylene glycol produced embryotoxic and teratogenic effects in animal feeding studies at high doses which were not maternally toxic.

**Other Adverse Effects:**

Not applicable

**Target Organ Effects:**

Lungs and eyes.

## Section 12: Ecological Information

<b>Ecotoxicity:</b>	Not applicable
<b>Persistence/Degradability:</b>	Not available
<b>Bioaccumulation/Accumulation:</b>	Not applicable
<b>Mobility:</b>	Not available

## Section 13: Disposal Considerations

<b>Waste Disposal Method:</b>	Do NOT dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage.
<b>United States:</b>	Dispose of in accordance with local, state and federal laws and regulations. RCRA Waste Codes: Not applicable
<b>Canada:</b>	Dispose of in accordance with local, provincial and federal laws and regulations.

## Section 14: Transport Information:

<b><u>U.S. Hazardous Materials Regulation (DOT 49CFR):</u></b>	Not regulated for transportation
<b><u>Canadian Transportation of Dangerous Goods (TDG):</u></b>	Not regulated for transportation
<b><u>ADR/RID:</u></b>	Not regulated for transportation
<b><u>IMDG:</u></b>	Not regulated for transportation
<b><u>Marine Pollutants:</u></b>	Not applicable
<b><u>ICAO/IATA:</u></b>	Not regulated for transportation

## Section 15: Regulatory Information

### USA

**TSCA Status:** All ingredients in the product are listed on the TSCA inventory.

**SARA Title III**

Sec. 302/304: None  
Sec: 311/312: Chronic  
Sec. 313: None  
CERCLA RQ: None

**California Prop 65:** This product may contain a substance known to the State of California to cause cancer [Crystalline silica – airborne particles of respirable size, traces of formaldehyde and vinyl acetate monomer].

### Canada

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the MSDS contains all the information required by the *Controlled Products Regulations*.

**WHMIS Classification:** D2A – Material Causing Other Toxic Effects– Due to possibility of inhaling Crystalline silica  
**(for workplace exposures)** during sanding operations.

**New Substance Notification Regulations:** All substances in this product are listed on Canada's Domestic Substances List (DSL).

**National Pollutant Release Inventory:** There are no NRPI reportable substances in this product.

**Section 16: Other Information**

**Prepared by:** LEHDER Environmental Services Limited  
704 Mara Street, Suite 210  
Pt. Edward, ON  
N7V 1X4  
www.lehder.com

**Phone:** 519-336-4101

**Preparation date:** April 30, 2003

**Revision Date:** June 26, 2006

**Revision Summary:** June 26, 2006: MSDS template updated to 16 section, ANSI Z400.1-2004 Standard for Material Safety Data Sheets Preparation. Revised product formulation; MSDS changed in all sections.

**Disclaimer:** While LEHDER Environmental Services Limited believes that the data set forth herein is accurate, as of the date hereof, LEHDER makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation and verification.

**Manufacturer's Disclaimer:** Information listed is believed to be accurate but not warranted or guaranteed.