

Roll-On Texture Refinish

MSDS#: 12-360 Effective Date: 30/3/03

PRODUCT IDENTIFICATION

GENERIC NAME: Flat Alkyd Paint

TRADE NAMES: ProFin™ Roll-On Texture Refinish
Fresh-tex

PRODUCT USE: Protective Coating

MANUFACTURER: General Paint Corp.
950 Raymur Ave.,
Vancouver British Columbia,
Canada V6A 3L5
Tel: 1-888-301-4454
Emergency # (604) 253-4022

SUPPLIER: BPB Canada Inc.
2424 Lakeshore Road West,
Mississauga, Ontario, Canada L5J 1K4
Telephone: (905) 823-9881
Fax: (905) 823-4860
Web Site: www.bpb-na.com

HAZARDOUS INGREDIENTS

AMORPHOUS 0.1-1% CAS #112945-52-5

FUMED SILICA LD50 of Ingredient (Species, Route)
3160 mg/kg (Oral, RAT)

HEAVY NAPHTHA (Hydrotreated) 15% CAS #64742-48
LD50 of Ingredient (Species, Route)
Not Available

MINERAL SPIRITS 8% CAS #8052-41-3
LD50 of Ingredient (Species, Route)
5000 mg/kg (Oral, RAT)
800 ppm (Vapour, RAT)

PHYSICAL DATA

PHYSICAL STATE: Liquid

SPECIFIC GRAVITY: 1.66

APPEARANCE AND ODOUR: Liquid with a solvent smell

BOILING POINT (°C): Not Available

FREEZING POINT (°C): Not Available

PH: Not Applicable

FIRE AND EXPLOSION DATA

FLAMMABILITY: Yes, flammable liquid

MEANS OF EXTINCTION: Alcohol foam, Carbon dioxide,
Dry chemical powder, polymer foam.

FLASHPOINT & METHOD: 60°C Closed Cup

EXPLOSION DATA: Not sensitive to impact or static discharges

HAZARDOUS COMBUSTION PDTS: Carbon monoxide, Carbon dioxide, Calcium oxide, Magnesium oxide, Nitrogen oxides.

REACTIVITY DATA

CHEMICAL STABILITY: Stable.

INCOMPATIBILITY: Yes, with Strong acids, Strong iodizing agents.

REACTIVITY: With heat, ignition sources

HAZARDOUS DECOMPOSITION PDTS: Carbon dioxide.

TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY: Skin contact, absorption, eye contact, inhalation, ingestion

ACUTE EXPOSURE: Heavy Naptha (Hydrotreated) has been known to cause headache, dizziness and other central nervous system effects. Mineral Spirits have been known to cause eye, nose and/or throat irritation, dizziness and dermatitis.

CHRONIC EXPOSURE: Mineral Spirits have been known to cause Narcosis, central Nervous System depression.

EXPOSURE LIMITS: Heavy Naptha (Hydrotreated): 1200 mg/m³. Manufacturer: ESSO
Mineral Spirits: PPM ACGIH

IRRITANCY: Amorphous fumed silica, Heavy Naptha (Hydrotreated) and Mineral Spirits are all skin and eye irritants.



Roll-On Texture Refinish

PRECAUTIONS FOR USE

PROTECTIVE EQUIPMENT:

Respirator (when sanding): Dust Mask
Gloves: Butyl Rubber
Eye: Splash Resistant

ENGINEERING CONTROLS:

Use mechanical ventilation to reduce exposure

LEAK AND SPILL PROCEDURE:

Wear adequate protective equipment. Contain spill with absorbent material and place in a suitable covered and labeled container for disposal.

WASTE DISPOSAL:

Check with Federal, Provincial and local government regulations and requirements for disposal.

HANDLING PROCEDURES EQUIPMENT:

Use in well ventilated area. Do not use with incompatible substances.

STORAGE REQUIREMENTS:

Store in cool, well-ventilated area out of direct sunlight.

SPECIAL SHIPPING INSTRUCTIONS:

TDG Shipping Name: Paint Classification: 3.3 Packing Group:
III Identification Number: UN1263.

FIRST AID EMERGENCY MEASURES

Inhalation:	Remove to fresh air. Get medical help if there is any breathing difficulty.
Ingestion:	Do not induce vomiting unless directed by a physician. If conscious and alert, give two glasses of water. Seek medical attention immediately.
Skin Contact:	Remove contaminated clothing (including shoes) and wash before reuse. Flush with large amounts of soap and water. If irritation persists, seek medical attention.
Eye Contact:	Flush eyes with large amounts of lukewarm water for 20 minutes while holding eyelids open or until irritation subsides. If irritation persists, seek medical attention.

Canada

BPB Canada Inc.

2424 Lakeshore Road West,
Mississauga, Ontario L5J 1K4
Telephone: (905) 823-9881
Fax: (905) 823-4860
E-mail: info@bpb-na.com
Web: www.bpb-na.com

Distributed by:

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, expressed or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

®™ Trademarks are the property of BPB plc or its affiliates and related companies

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

© 2005 BPB Canada Inc. Printed in Canada on recycled paper. ♻ September 2005

