

Architectural Abstract

Cashmere® Integrated Accents NODULAR ACOUSTICAL CEILING PANELS


- Upscale appearance.
- Decorative pattern scoring without costly, labor-intensive accessories.
- Factory applied vinyl latex paint.
- Patterns ranging from classical to contemporary.
- Allows incorporation of lighting and speaker options.
- BioShield™ feature included as standard feature for added mold and mildew resistance.

See reverse side for additional product specifications.


Item Number	Nominal Size (Inches)	Edge Detail	UL Classified		LR	Sq. Ft. Per Carton
			NRC	CAC		
Safetone® Class A						
CA-901	24 x 24 x 3/4	Tier Reveal	.60	35	.82	56
CA-903	24 x 24 x 3/4	Narrow Reveal	.60	35	.82	56
CA-904	24 x 24 x 3/4	Tier Reveal	.60	35	.82	56
CA-907	24 x 24 x 3/4	Neo	.60	35	.82	56

ASTM E 1264 Classification: Type III, Form 1, Pattern E K


Edge Detail Options



Narrow Reveal Edge
(Beveled) 5/16" Grid




Tier Reveal Edge
5/16" Grid




Neo Reveal Edge
5/16" or 15/16" Grid


Scoring Options




Tier Reveal Edge
CA-904



Tier Reveal Edge
CA-901



Narrow (Bevel)
Reveal Edge
CA-903



Neo Reveal Edge
CA-907



BioShield™

BioShield treatment **included** for added mold and mildew resistance.



Popular Applications:

- Conference Centers • Resorts • Hospitality • Retail • Education
- Restaurants • Healthcare • Offices • Airports • Galleries



PRODUCT SPECIFICATION DETAILS

ACOUSTICAL CEILING SYSTEMS

09500

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type III
2. Form 1
3. Pattern E K
4. Lightly textured nodular lay-in panels
5. Size 3/4" thick x 24" x 24"
6. Edge Detail: [Bevel Reveal] [Tier Reveal] [Neo Reveal]
7. Noise Reduction Coefficient (NRC) .60
8. Ceiling Attenuation Class (CAC) 35
9. Light Reflectance Coefficient (LR) .82
Light Reflectance Designation LR-1
10. Color White
11. Flame Spread Classification Class A
12. Manufacturer, subject to compliance with requirements of this specification, BPB
13. Product Name Celotex® Brand Cashmere® Integrated Accents

Distributed by:

USA

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Canada

BPB Canada Inc.
Architectural Products Sales Division
6715 Ogdendale Road SE
Calgary, Alberta T2C 2A4
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Outside North America

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Phone: +1-813-286-3900
Fax: +1-813-286-3908
E-mail: international@bpb-na.com
Web: www.bpb-na.com

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

©™ Trademarks are the property of BPB plc or its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

©2005 BPB America Inc. Printed in U.S.A. Form LCD-4705 Rev. E/W/0505

