

MSDS Name: Level V Wall and Ceiling Primer / Surfacer
MSDS Number: PF4511-01
Version Number: 0009
MSDS Date: 06/15/06



MATERIAL SAFETY DATA SHEET

Section I - Product and Company Information

Product Name: Level V Wall and Ceiling Primer / Surfacer
CAS Number: Mixture
Hazard Rating: Health: 1 Fire: 1 Reactivity: 0 PPI: E
EPA Registration: NA

Company Identification: Acrylic Technologies, Inc.
P.O. Box 3425
Sunriver, OR 97707

Contact: CUSTOMER SERVICE
Telephone/Fax: (541) 617-9494 / (541) 617-9595
Emergency Phone (24 Hour): **INFOTRAC**
(800) 535-5053

Product Class: Waterbase Paint
Trade Name: Level V Wall and Ceiling Primer / Surfacer
Product Code: PF4511-01

Section II - Ingredient And Hazard Information

NFPA (USA)	WHMIS (Canada)	Transport Symbol
NA	NA	NA

Hazardous Ingredients:

CAS Number % TSCA Health Fire React PP
(No hazardous ingredients known at this time.)

Section III - Hazards Identification

Primary Routes of Entry: Ingestion and/or inhalation.

Carcinogenicity: This product does not contain any substance(s) listed as a carcinogen by NTP, IARC, or OSHA.

Acute (Short Term) For Product: EYES: Causes irritation.
SKIN: May cause skin irritation upon prolonged or repeated contact.
BREATHING: Causes slight irritation to nose and throat.
SWALLOWING: Ingestion may cause nausea, vomiting, diarrhea.

Chronic (Long Term) For Product or Components:
Prolonged or repeated breathing of sprays, mists, or dusts in excess of the suggested TLV may cause nasal and respiratory irritations.

MSDS Name: Level V Wall and Ceiling Primer / Surfacers
MSDS Number: PF4511-01
Version Number: 0009
MSDS Date: 06/15/06

Permissible Exposure Level for Product:

No Threshold Limit Value (TLV) has been established for the product. Current Adopted Values listed by ACGIH suggests a TLV of 10 mg/m³ as Inhalable Particulates Not Otherwise Classified for sprays, mists or dust particulates generated during application or handling exposures.

Section IV - First Aid Measures

- If In Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. If irritation continues, see a physician.
- If On Skin:** Flush skin with water.
- If Swallowed:** Induce vomiting. Call a physician immediately. Give large amounts of water or milk. Never give anything by mouth to an unconscious or convulsing person.
- If Breathed:** Remove person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

Section V - Fire-fighting Measures

- Flammability Class:** IIIB
- Flash Range:** >200F
- Explosive Range:** Not Applicable.
- Extinguishing Media:** Extinguishing media: Product is non-combustible.
- Special Firefighting Procedures:** Use self-contained breathing apparatus with full face piece.
- Unusual Fire & Explosion Hazards:** None.

Section VI - Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

- Small Spills:** Contain spill immediately. Use inert material to absorb spilled material. Place absorbed spill into secure container for removal.
- Large Spills:** Use caution; spilled material may be extremely slippery. Contain spill immediately and prevent from entering the sewer system. Use an inert material to absorb spilled product.
- Note:** Rinsing this material down a sanitary sewer system can cause negative impact on monitoring systems. Contact local sewer authorities before attempting any discharges.

Section VII - Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- Protect From Freezing:** Store above 40°F. Frozen product may be irreversibly damaged. Keep container closed when not using. Agitate before using.

MSDS Name: Level V Wall and Ceiling Primer / Surfacers
MSDS Number: PF4511-01
Version Number: 0009
MSDS Date: 06/15/06

Section VIII - Exposure Controls/personal Protection

Occupational Exposure Limits:

ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL OSHA PEL

- Respiratory Protection:** Use an approved MSHA or NIOSH respirator for nuisance mists, dusts, or sprays.
- Ventilation:** Use adequate ventilation to keep airborne concentrations below the exposure standard listed in Section II and/or Section V.
- Protective Gloves:** None normally required. Use is advisable.
- Eye Protection:** Wear approved splashproof chemical goggles. In a controlled environment where eye contact is minimal, Safety glasses with side shields may be sufficient protection.
- Other Protective Equipment:** Avoid contact with clothing, dried product may be irremovable.

Section IX - Physical And Chemical Properties

- Form:** Liquid
- Appearance/Color:** White
- Odor:** Mild
- Solubility (in water):** Dispersible
- pH Value:** 8.5 - 10.0
- Boiling Range:** (Water) 212°F (100°C)
- Vapor Pressure (mmHg):** (Water) 17. @ 68°F (20°C)
- Melting Point:** Not Available
- Evaporation Rate:** Unavailable
- Vapor Density:** Non Volatile
- Partition Coefficient:** Not Available
- % Volatile Volume:** Including Water 60.8%
- Specific Gravity:** 1.42633
- VOC:** See Section XVI
- Molecular Weight:** Mixture

MSDS Name: Level V Wall and Ceiling Primer / Surfacers
MSDS Number: PF4511-01
Version Number: 0009
MSDS Date: 06/15/06

Section X - Stability and Reactivity

Stability: This product is stable

Hazardous Polymerization: Hazardous polymerization will not occur

Incompatability: None

Conditions To Avoid: Acids, strong oxidizing agents.

Hazardous Decomposition Products:
Thermal decomposition or burning may produce carbon monoxide and/or carbon dioxide.

Section XI - Toxicological Information

Lethal Dose Information (ppm)

Additional Toxicological Data For Product And/or Ingredients:
None known for product.

Section XII - Ecological Information

ECOLOGICAL INFORMATION FOR PRODUCT AND/OR INGREDIENTS:
Aquatic toxicity not available.

Section XIII - Disposal Considerations

EPA Hazardous Waste Number: None

WASTE DISPOSAL METHOD: Product must be disposed of properly under Federal/State regulations for industrial waste. Disposal to a landfill may be permitted pending compliance with 40 CFR 264.314 & 265.314. This product when spilled or disposed of is a non-hazardous waste as defined in RCRA regulations (40 CFR 261).

Section XIV - Transport Information

UN Number: None

UN Pack Group: NA

UN Class: NA

ICAO/IATA Class: None

DOT Hazard Class: Not Hazardous

MSDS Name: Level V Wall and Ceiling Primer / Surfacer
MSDS Number: PF4511-01
Version Number: 0009
MSDS Date: 06/15/06

Section XV - Regulatory Information

EEC Classification: Irritant

This product is not a listed hazardous substance.

Section XVI - Other Information

Additional Precautions And Notes:

Do not dilute or mix with other materials unless advised by supplier.

VOC Information:

A Certified Product Data Sheet (CPDS) as outlined under Title 40 Part 63, Subpart JJ, Section 63.801 Definitions, detailing VOC content, will be available upon request.
VOC content: 0.14 lbs per gallon.